



LANCASTER WATER TREATMENT

Clear-Flo POINT-OF-USE FILTER: 210-POU-05-P

40 YEARS OF QUALITY DESIGN AND DEVELOPMENT HAVE RESULTED IN NEW MATERIALS, NEW MOLDING METHODS, AND EXPERTISE TO CREATE THE HIGHEST QUALITY POINT OF ENTRY CARTRIDGE FILTRATION DESIGNS AVAILABLE.

FEATURES

- Suitable for cartridges with 2.5"OD.
- Fit to double open ended cartridges.
- 10" length
- Clear sump with a pressure rating at 125 psi.
- Stainless Steel inserts 3/4" NPT connection
- Pressure-relief feature that includes an O-ring seal, no spring is used that can result in a water leak.
- Accessories included are: filter wrench, wall mount brackets, lubricant for housing O-ring.

FILTER PACKAGE FOR FULL-FLOW APPLICATIONS

Specialty designed filter housings for wide range of applications.

Lancaster's Three Piece housings are designed to work with standard filter cartridges with an outer diameter of 2.5" (from 2.0" to 2.5" applicable) and come with a pressure rating of 125 PSI. The design can accommodate double open ended cartridges. The housing is designed to compress the O-ring evenly between the housing and the head assembly, without stretching or distorting. The result is a more even and consistent seal reducing O-ring damage that could result in a leak.

Available with NPT tapered Stainless steel insert IN/OUT connections in 3/4", the housings adapt to any point-of-use application in water filtration.

Activated carbon block made from coconut shell, providing fine sediment filtration and reduction of chlorine, taste, odor (CTO), volatile organic compounds (VOC), and providing heavy metal reduction.

Lancaster is driven to providing our customers with the best available products to meet their filtration requirements. This is done by using the most advanced manufacturing and design methods. The international patents received come from a constant commitment to research and develop that result in new and innovative products.

CLEAR-FLO POINT-OF-USE FILTER PACKAGE



Clear-Flo POINT-OF-USE FILTER PACKAGE

LANCASTER OFFERS THE MAXIMUM FOR: PRODUCTIVITY, RELIABILITY, AND FLEXIBILITY

APPLICATIONS

- Replaces expensive grocery store POU filters
- Polishes cold water at main faucet without needing an additional drinking water faucet

Model No.	Housing			Cartridge	
	Description	Flow Rate	In/Out (NPT)	Description	Micron
Point Of Use					
210-POU-05-P	Housing - 210-H-75SS-C-KIT			Cartridge - 210-C05-CA	
	2 x 10" Three Piece Filter Housing	8 GPM	3/4" Stainless Steel	Activated Carbon Block (Coconut Shell)	0.5 Micron

SPECIFICATIONS


MATERIALS:

- Heads: reinforced polypropylene.
- Ring nut: reinforced polypropylene.
- Clear sumps: PET.
- O-rings: EPDM.

WORKING CONDITIONS:

- Working pressure: Max 125 psi (8.6 bar).
- Working temperature range: Min 39.2°F (4°C) - Max 113°F (45°C).

CERTIFICATIONS



Housings certified by IAPMO RT to NSF/ANSI 42, 61, 372

- lead free, CSA B483.1. In compliance with drinking water regulations, USA and Canada

