# LANCASTER LAUNDRY TRAY WASTE WATER PUMPS



**LANCASTER X99 pumps** are designed for gravity feed pumping applications. They will remove clean or waste water from a laundry tray/tub/sink in an area with no floor drains. These pumps can be located below the laundry tray/tub/sink and will pump waste water to an overhead or remote drain line. No need to break through the floor for unsanitary sumps and sump pumps.

**Applications include:** laundry tray, wet bar sink, lavatory sink, air conditioning condensate, dehumidifier water removal.


**NOT recommended for** flammable or explosive liquids or liquids with solids, strong acids or caustics. **Maximum water temperature 130°F.** 

### **Automatic Operation**



MODEL	X99A33	X99A50		
HP	1/3	1/2		

## **Manual Operation**



MODEL	X99M33	X99M50		
HP	1/3	1/2		

#### X99A SPECIFICATIONS

- Single phase, 115v, thru-bolt motor with automatic reset thermal overload protector.
- 8 ft. 16/3 SJTOW cord set with plug.
- CL30 gray iron discharge casing.
- Glass filled polypropylene semi-open impeller.
- Buna-N mechanical rotary seal and o-ring.
- Neoprene gaskets.
- · Cast aluminum suction housing.
- Mechanically-activated switch.
- Inlet size: 1½" NPT Female.
- Discharge size: 1" NPT Female.
- Vent size: ½" NPT Female

#### **X99M SPECIFICATIONS**

- Single phase, 115v, thru-bolt motor with automatic reset thermal overload protector.
- 8 ft. 16/3 SJTOW cord set with plug.
- CL30 gray iron discharge casing.
- Glass filled polypropylene semi-open impeller.
- Buna-N mechanical rotary seal and o-ring.
- CL30 gray iron suction cover.
- Inlet size: 1½" NPT Female.
- Discharge size: 1" NPT Female

		TOTAL HEAD IN FEET				SHUT OFFHEAD		
MODEL	НР	5'	10'	15'	20'	25'	30'	MAX. FT AT
		GPM				0 GPM		
X99A33 X99M33	1/3	31	25	18	9	-	-	25'
X99A50 X99M50	1/2	36	32	27	19	12	7	35'

